

Selva Collection



Selva is a stunning wood-look porcelain collection that captures the essence of nature's beauty. With a range of shades from light wood to dark grey, Selva offers a versatile palette to suit any design preference. Its aesthetic mimics organically weathered wood, bringing a natural appeal and charm to any space.


The collection's textured surface and authentic look create a warm, inviting atmosphere, making it an ideal choice for those seeking both elegance and durability in their interiors.



Aspen




Birch




Oak



Ash



Magnolia



Mahogany



Color/Finish/Size

10"x72"

Aspen Natural	DIG1072126
Birch Natural	DIG1072127
Oak Natural	DIG1072130
Ash Natural	DIG1072125
Magnolia Natural	DIG1072128
Mahogany Natural	DIG1072129

All sizes are nominal; for technical information refer to our website stonepeakceramics.com

Packaging	Box/Pcs	Box/Sq.Ft.	Pallet/Box	Pallet/Sq.Ft.	Weight Lb/Sq.Ft.	Thickness (mm)
10"x72"	4	19.59	30	587.7	3.6	8.0

DISCLOSURE

Colors depicted are for reference only; please refer to live product for an accurate representation before making your final decision. Please contact your sales manager or customer service representative for more information.



1. PRODUCT NAME

SELVA COLLECTION

TECHNICAL DATA SHEET

2. MANUFACTURER

Stonepeak Ceramics, Inc.

720 N. Franklin St., Ste 500, Chicago, IL 60654 US

Production Factory:

238 Porcelain Tile Dr., Crossville, TN 38555 US

Telephone: 312.506.2800

Email: info@stonepeakceramics.com

Website: stonepeakceramics.com

3. PRODUCT DESCRIPTION

Selva collection offers a natural wood-look granulated porcelain planks with high durability and low maintenance in 10"x72" size to design more airy and open spaces.

Recommended Applications:

Ideally suited for commercial and residential floors and walls.

Finishes/Textures:

- Thru Color, Honed
- Rectified

Size/Thickness:

10" x 72" x 5/16" nominal *(8 mm)

**Denotes work size per ISO 10545-2.*

Recommended Grout Joint: 3/32" or greater.

Grout joints of 1/8" inch or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

For patterns with running bond/brick joints, Stonepeak recommends a maximum of 33% offset.

For patterns with running bond/brick joints patterns StonePeak recommends a maximum of 33% offset.

4. TECHNICAL DATA

Physical Properties	ASTM Test	Industry Standards	StonePeak Results
Water Absorption	C373	Impervious < 0.5%	≤ 0.1%
Thickness Dimension	C499	Range ±0.04 Inc. Max	≤ ±0.04 Inc.
Facial Dimension	C499	± 0.25%	≤ ±0.25%
Warpage Average Diagonal	C485	±0.40%	≤ ± 0.40%
Warpage Average Edge	C485	±0.40%	≤ ±0.40%
Wedging Average	C502	±0.25%	≤ ±0.25%
Bond Strength	C482	≥ 50 psi	≥ 200 psi
Breaking Strength	C648	≥ 250 lbf	≥ 400 lbf
Hardness (Mohs)	Scratch Test (No regulated)	Range 0-10	≥7
Visible Abrasions Resistance for Glaze Tiles	C1027	No Requirement Range 0 – 5	Class 4
Frost Resistance	C1026	No samples must show alterations to surface	No Evidence of Damage
Chemical Resistance	C650	No Requirement Range E- A	Class A
Stain Resistance	C1378	No Requirement Range E- A	Class A*
DCOF	BOT 3000	≥ 0.42*	≥ 0.42*
Aesthetic Class/Shade Rating	Visual Evaluation Shade & Texture	No Requirement Range V0-V4	V2

DCOF*: all values given are for matte or honed material. No values are given for polished material. Dolce Italia does not recommend polished surfaces in areas subject to exposure from grease, oil or water.

5. INSTALLATION

Surface preparations:

All installation work using Stonepeak Ceramics' tiles will conform to the standards set forth in the latest version of ANSI A108/118 and/or the TCNA Handbook for Ceramic Tile installations.

All substrates should be between 40 degrees F and 90 degrees F and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds as per ANSI A108.01.

Deflection:

Substrate must conform to all state and local building code requirements and ANSI A108.01 for maximum allowable substrate deflection

Movement joints:

Movement joints shall be provided throughout the tile and work will conform to ANSI Specification A108.01-3.7; A108.02 – 4.4. and TCNA Details EJ171.

Installation or setting materials:

Setting materials used will conform to the ANSI 118.4 standard or greater and be recommended by the selected manufacturer for the installation & setting materials for ceramic or porcelain tile based on the application requirements.

6. AVAILABILITY AND COST

Selva is available from selected distributors of ceramic tile.

To find accessible information of delivery and product costs for your area, please contact your nearest Stonepeak Ceramics distributor.

7. WARRANTY

Stonepeak Ceramics guarantees that its products will be free of manufacturing defects and they will meet or exceed the performance specifications set forth in ANSI 137.1.

For further information and details please contact your nearest Stonepeak Ceramics Distributor for a written copy of the warranty information.

8. MAINTENANCE**Care and Maintenance Recommendations Guide.**

Please refer to **Stonepeak Ceramics Care and Maintenance Recommendations Guide** for all technical information as to the care of this collection.

9. TECHNICAL SERVICES**Technical Assistance**

Guide Specifications, literature, SDS, tile samples, details and installation procedures are all available for your use or libraries.

Please contact your nearest Stonepeak representative for catalogues or physical samples.

Continued Education Programs are available – 1- or 2-hour **HSW Learning Units** – contact Stonepeak Ceramics' main office to set up a presentation.

10. FILING SYSTEMS**Selva Collection**

Aspen



Birch



Oak



Magnolia



Ash



Mahogany

11. ENVIRONMENTAL CERTIFICATIONS

Stonepeak proudly contain factory and product certifications:

**12. RECYCLED CONTENT**

Products certified by Bureau Veritas. Please ask to see certifications.