


COLORS




Crater




Valley




Shale



Pewter



Dusk



Flint


AVAILABLE SIZES



63" x 126"




48" x 110"




48" x 48"



36" x 36"



24" x 48"



24" x 24"



12" x 24"



Crater
4" Hexagon
Mosaic



Valley
4" Hexagon
Mosaic



Shale
4" Hexagon
Mosaic



Pewter
4" Hexagon
Mosaic



Dusk
4" Hexagon
Mosaic



Flint
4" Hexagon
Mosaic

FINISH

HONED RECTIFIED
ORGANIC MATTE RECTIFIED
VINTAGE RECTIFIED

THICKNESS

6 mm - 63" x 126" & 48" x 110"

9 mm - 48" x 48", 36" x 36",
24" x 48", 24" x 24", 12" x 24"


20 mm - 36" x 36" & 24" x 48"

INSTALLATION & MAINTENANCE

Recommended Grout Size - 1/8"

For regular cleaning, use a neutral liquid detergent with a soft sponge or microfiber cloth. Persistent stains can be removed with a slightly abrasive sponge; if necessary, use a specially formulated stain remover.

TECHNICAL DATA



D.C.O.F.
WET
HONED - > 0.50
ORGANIC R10 - > 0.60
VINTAGE R11 - > 0.75
ANSI A 326.3

WATER
ABSORPTION
< 0.1%
ASTM C373

CHEMICAL
RESISTANCE
HONED - CLASS A | CLASS B
ORGANIC R10 - CLASS A
VINTAGE R11 - CLASS A
ASTM C650

FROST
RESISTANCE
PASS
ASTM C1026

BREAKING
STRENGTH
6mm - > 310 lbf
9mm - > 570 lbf
20mm - > 2925 lbf
ASTM C648

ABRASION
RESISTANCE
HONED - < 140mm³
ORGANIC R10 - < 120mm³
VINTAGE R11 - < 120mm³
ASTM C1027



SERENA

