

# SERENTINA™

GLASS & STONE MOSAIC

MOSAIC



AMERICAN OLEAN®  
PROVEN IN TILE™

AMERICANOLEAN.COM

# SERENTINA™

Crafted with eye-catching glass and stone, Serentina by American Olean® puts luxurious style within reach. Featuring striking geometric designs in three versatile patterns and six unique color blends, the collection offers flexibility to perfectly accent residential spaces. Ideal for backsplashes or tub and shower surrounds, Serentina can also be used as borders or liners to add a subtle touch of elegance.

Cover photo features Serentina Zen herringbone mosaic on backsplash and Theoretical™ Logical Gray 12 x 24 on the floor.  
Above photo features Serentina Zen herringbone mosaic on backsplash.

# SERENTINA™

GLASS & STONE MOSAIC

## HERRINGBONE

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97



SOLITUDE SA98

## BLOCK RANDOM

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97



SOLITUDE SA98

## RANDOM INTERLOCKING

---



BLISS SA93



TRANQUILITY SA94



ZEN SA95



ACCORD SA96



COMPOSURE SA97




SOLITUDE SA98

# SERENTINA™

GLASS & STONE MOSAIC

## SIZES

			THICKNESS	SQ. FT./ CARTON	PIECES/ CARTON
	Herringbone Glass & Stone Mosaic ■	11-1/2" x 12-3/4" Sheet (29.21 cm x 32.39 cm Sheet)	1/4"	14.10	15
	Block Random Glass & Stone Mosaic ■	12-1/4" x 11-7/8" Sheet (31.12 cm x 31.18 cm Sheet)	1/4"	15.15	15
	Random Interlocking Glass & Stone Mosaic ■	13-1/4" x 11-3/4" Sheet (33.66 cm x 29.85 cm Sheet)	1/4"	14.70	15

■ Mesh-mounted

## INSTALLATION & PRICING

**RECOMMENDED GROUT JOINT:**  
Mosaic: 1/8"

**RELATIVE PRICING:** Low to Medium

**SHADE VARIATION**



## PERFORMANCE CHARACTERISTICS

	ASTM#	MOSAIC RESULT
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4

For additional information on test results, visit us at: [americanolean.com/information/TestResults](http://americanolean.com/information/TestResults).

## USAGE

FLOORS	WALLS	COUNTERTOPS
	W	

## APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

## NOTES

For additional information refer to "Factors to Consider" at: [americanolean.com/Factors](http://americanolean.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE  
©2017 AMERICAN OLEAN (06/17)



AMERICAN OLEAN®  
PROVEN IN TILE™